




Spectrum III Hybrid

Intelligent OEM Insert Reader Module.

MSR and EMV hybrid insert reader. Smart card read and write capabilities and vertical or horizontal mounting options make this reader perfect for multiple environments.

Key Features

- ✓ Reads & decodes up to 3 tracks of magnetically-encoded information
- ✓ Spring loaded magnetic head ensures optimal contacts with cards
- ✓ Can be configured to read all tracks or selected tracks from magnetic stripe
- ✓ Reads ISO 7810 & 7811 media
- ✓ Can output data with a terminating character up to nine prefix & postfix characters

Contact Us for More Information on our Payment Solutions

- (714) 761-6368
sales@idtechproducts.com
10721 Walker Street
Cypress, CA USA 90630-4720
- ISO 9001 Certified
ISO 14001 Certified



Electrical

Interface RS232, USB PC/SC & USB RS232

Power +5 VDC/70mA / +5 VDC/80mA (power adapter regulated 5 VDC/500mA or equivalent)

Environmental

Humidity Max 95% non-condensing

Operating Temperature 0°C to 55°C

Storage Temperature -30°C to 65°C

Mechanical

Dimensions 117 mm (L) x 101 mm (W) x 9.88 mm (H)

Media Format ISO 7811, F2F media with magnetic coercivity of 300-4,000 oersted can be read

Media Thickness 0.635 mm to 0.889 mm

Warranty One year, parts & labor



Corporate Headquarters

☎ (714) 761-6368

✉ sales@idtechproducts.com

📍 10721 Walker Street
Cypress, CA USA 90630-4720

Europe, Middle East, Africa

☎ 714-761-6368

✉ emea@idtechproducts.com

Latin America

☎ 5511-3079-2255

✉ latam@idtechproducts.com

Asia Headquarters

☎ 886-3-326-5988

✉ asia@idtechproducts.com

Visit Us:
IDTECHProducts.com

